

Price Schedule for Goods IB No. 2024-044

Procurement of 10-Wheeler Self Loading Truck with Boom

For Goods Offered from Within the Philippines

Nan	ne of Bidder:	Project ID No.:					Page of			
1	1 2	3		4	J 5	I 6	7	<u> </u>	9	10
Iten		Country of origin	Unit of Measure	Quantity	Unit price ExW per item	Transportation and all other costs incidental	Sales and other taxes payable if Contract is	Cost of Incidental Services, if applicable, per	Total Price, per unit	Total Price delivered Final Destination
						to delivery, per item	awarded, per item	item	(col 5+6+7+8)	(Col. 9) x (Col. 4)
1	Self Loader with Boom Crane MT		Unit	1						
	*ENGINE: DIESEL engine, 6 Cylinder In-Line, Common-Rail									
	Direct Injection System, Euro 4									
	Engine Displacement – atleast 7,790L - 200L Fuel Tank Capacity,									
	Max. Output KW (PS)/rpm: atleast 206(280.0)/ 2,400									
	Max. Torque N-m (kg-m)/ rpm: atleast 882(90.0)/ 1,450									
	TIRE Size: atleast 11R22.5-16PR, 11 numbers of tires including spare tire, Single Deferential									
	BRAKE: Drum Type, full air brake Alternator (V-A): 60A									
	SUSPENSION: Multi-Leaf Spring									
	CONVENIENCE: Power Window and Auto Door lock, Single									
	Aircon and Radio									
	Gross Vehicle Weight: atleast 26,000kgs, Payload 18,995kgs,									
	2. BRAND NEW HEAVY DUTY DROPSIDE BODY									
	Body Dimension: (lxwxh) 28' x 8									
	*. Floor Runner : C channel Steel bar-6", atleast size 6mm x 3" x									
	6"; with flat belt, angle brace and bracket.									
	*Flooring: MS steel checkered plate, size atleast 5.0mm thick.									
	EPOXY black paint floor finished.									
	* Floor Joists: casted steel channel bar-3", size atleast 4.5mm thick x2"x5"x2".									
	*Floor Sills : casted steel channel bar-4", size atleast4.5 mm									
	thick x2"x5"x2";		ļ							
	*. LED Lights: on each side of the drop side									
	* Rear Ramp : Heavy duty Manual Ramp		<u> </u>							
	* Mudguard : Flat design BI steel plate, size atleast 1.50mm									
	thick, with flat steel bracket.									

	<u> </u>		<u> </u>				
*Painting : Automotive polyurethane (Nippon) paint body							
finished							
*Anchorage : BI steel angle brace & District mounting							
bracket and 3/4"" U-bolts with high nuts.							
3.Body:TELESCOPIC CRANE IN HEAVY DUTY DROPSIDE							
*Self-Loader with Crane: Unic URU 554HRKK-TH (5-ton							
Capacity) URU554HRKK-TH							
Maximum Lifting Capacity atleast 5,050 kg. At 2.5 m.							
Maximum Hook atleast Height 12.7 m.							
Maximum Working Radius atleast 10.63 m. Boom Length 3.6							
m. to 10.87 m.							
Boom Sections 4							
Boom Raising Angle Min. 1° to Max. 78°							
Slewing Angle 360° Continuous							
Winch wire rope :atleast IWRC 6 X Fi (29)							
Wire rope diameter & length: atleast 10mm x 56m/							
10mm x 69m/10mm x 80.5m							
AL AMOUNT IN NUMBERS							
TAL AMOUNT IN WORDS							
Name:					_		
Legal Capacity:							
Signature:							
Duly Authorized to Sign Bid for and on Behalf of :							